



SAFE WORK PRACTICE

| | |
|--|--|
| TITLE | Stringing Pipeline Pipe |
| GENERAL | Protecting workers from injuries associated with stringing operations |
| APPLICATION | Pipe is loaded and transported from the place of manufacture, coating or stockpile to the pipeline right-of-way where it is off-loaded and strung. |
| POTECTIVE MECHANISMS | Safe work procedure Permit system Barricades and warning signs PPE ERP (Emergency Response Plan) Rigging & Hoisting Procedure Pipe Blocking Procedure |
| SELECTION AND USE | As per safe job procedure Provincial OH&S Legislation |
| SUPERVISOR RESPONSIBILITY | Supervisors are responsible to facilitate and/or provide proper instruction to their workers on protection requirements and training Hazard assessment Site inspection |
| WORKER RESPONSIBILITY | <ol style="list-style-type: none">1. Ensure you remain within the operators' line of vision.2. Watch your step.3. Know the proper hand signals.4. Know pinch points.5. Do not stand between pipe and equipment.6. Do not stand between pipe and ditch.7. Do not walk under suspended loads.8. Ensure proper rigging & hoisting safe work procedures are followed.9. Ensure proper pipe blocking safe work procedures are followed. |
| <p>* The information presented in this publication is intended for general use and may not apply to every circumstance. It is not a definitive guide to government regulations and does not relieve persons using this publication from their responsibilities under applicable legislation. The Alberta Construction Safety Association does not guarantee the accuracy of, nor assume liability for, the information presented here. Individual counselling and advice are available from the Association.</p> | |